



**MINGPOWERS**

**M-C900 Technical Data sheet**



**Professional Genset Manufacture On Your Side  
Fujian Minghui Mech & Elec Co., Ltd.**

## DIESEL GENERATOR

### Powered by **Cummins Engine & Leroy somer** Alernator

#### STANDARD SPECIFICATION

Three phase four wire, output voltage 400V/230V, 50HZ, between 0.8 lagging, protection capability according with the standard of NAME1 and IP23.

#### General Features:

Composed of **Cummins** diesel engine and **Leroy somer** alternator

Oil and fuel filter fitted, water separator

Lube-oil drain valve fitted

Electric Starter Charge motor 24 VD.C

Water-cooled

Δ baseskid fuel tank

Auto start

Optional soundproof and weatherproof canopy

Δ 3 pole MCCB Delixi breaker/Optional ABB

Δ Operation & Maintenance manual

Special Integrated Steel Base tank and sprayed overall in gloss enamel paint

#### Voltage Regulation

Voltage regulation maintained within  $\pm 0.5\%$

Between 0.8 and 1.0 lagging and unity

From no load to full load

At speed droop variation upto 4.5%

#### Frequency Adjustable Ratio

Change load from 0-100%, within 1.0% ( electric speed regulator), within 4.5% ( mechanical speed regulator)

#### Frequency Undulation

load from 0-100%, frequency undulation within 0.25%

No load wire volts max undulation ration\ within 1.8%

Three Phrase balanced load in the order of 5%

#### Effect factor of Telecom

TIF better than 50

THF to IEC60034 Part 40 better than 2%



#### 50HZ, 1500RPM, 3-PHASE, 400V/230V

| Gensets model | Power output(KVA) |            | Power output (KW) |            | Cummins Engine Model | Leroy somer Alternator |
|---------------|-------------------|------------|-------------------|------------|----------------------|------------------------|
|               | PRP               | ESP        | PRP               | ESP        |                      |                        |
| <b>M-C900</b> | <b>800</b>        | <b>900</b> | <b>800</b>        | <b>640</b> | <b>KTA38G2A</b>      | <b>LSA49.1M75</b>      |

Note:

(1) Available in the following voltages: 220V-240V AND 380V-415V(440V)-50HZ

(2) PRP: Prime Power-Continuous duty operation, under variable load 24/24-h-10% overload permissible 1 hour/12hours.

(3) Rating Definitions (Operation at Altitude 1000m, Ambient temperature 40 )Continuous Power. These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power.

## Engine & Alternator

**ENGINE**--Industrial 4 stroke cooled diesel engine complete with air,fuel and oil filters,electric starting and charging equipment,engine protection against low water level.

**ALTERNATOR**--Brushless,self exciting,self regulation,sreen protected,drip proof rated in accordance with IEC60034.Voltage regulation maintained within  $\pm 0.5\%$  from no load to full load.between 0.8 lagging and unity.All standard voltages available.

**COOLING**--Radiator and colling fan complete with protection guards,designed to cool engine at specified output in air temperatures upto 45 ,radiators suitable for higher temperatures are available.Low water level protection fitted as standard.

**ELECTRICAL SYSTEM**--24V upto.Axial type starter motor,battery charging alternator,high capacity lead acid battery,and battery tray mounted on the generator base frame,and heavy duty interconnecting cable with terminations.

**EXHAUST SYSTEM**--Heavy duty industrial exhaust silencer with flexible piping.

## Technical Data Sheet

### Generating sets model:

**400V,50Hz,1500 rpm**

|                            |                            |                    |
|----------------------------|----------------------------|--------------------|
| Engine Model:              | Cummins KTA38G2A           |                    |
| Type                       | 12 cylinder,4 cycle diesel |                    |
| Aspiration                 | Turbocharged               |                    |
| Bore/Stroke                | mm                         | 159X159            |
| Compress the ratio         | 13.0:1                     |                    |
| Cooling system             | Water-cooled               |                    |
| 100% Load Fuel Consumption | L/H                        | 191                |
| Engine Speed/Frequency     | RPM/Hz                     | 1500/50HZ          |
| Rated Output               | kw/Bhp                     | 813/1090           |
| Exhaust air flow           | (m3/min)                   | 588                |
| Coolant Capacity           | L                          | 194                |
| Starting System            | Electric 24 volt DC        |                    |
| Displacement               | L                          | 37.8               |
| Lubricant system Capacity  | L                          | 135                |
| Battery Volatge / Capacity | 24VDC                      |                    |
| Governing Type             | Electrical (GAC governor)  |                    |
| Exhaust Gas Temperature    | 552                        |                    |
| Exhaust Gas flow           | m3/min                     | 158.6              |
| Noise level                | dBA@7m                     | 90dBA(canopy type) |

### Genset Option Features

Low fuel level alarm shutdown  
Automatic Fuel Filling System  
Engine oil feeding and drain pump  
Auto Transfer Switch( ATS)  
Parallel control panels  
Circuit Breaker MCCB & ACB  
Remote Control Panel  
weatherproof/soundproof Canopy  
Trailer type Gensets

### QUALITY STANDARDS

ISO9001:2000,ISO14000,ISO3046  
ISO8528 BS4999  
BS5514,AS1359,ICE34  
CE Compliance

### Gensets Dimensions & Weight

Open type:L\*W\*H,mm  
4450×1750×2350  
Enclosure type:L\*W\*H,mm  
HQ container type

## Alternator Technical data

### Leroy somer

Bruxhless,self exciting  
Class "H" insulation  
Standard degree of protection is IP23  
self regulating  
With fan cooling  
Resist Humid grease  
AC excitation,roating rectification tube  
Stator grease insulation covered  
Rotator and exciation high polymer,Resist the corruption of oil and acid  
Rotator ballance is in accordance with BS5625 standard 12.5  
High-quality lubrication sealed long-time bearing  
Rotator sillicon steel close tight

|                           |                        |
|---------------------------|------------------------|
| Exciter                   | Brushless              |
| Cooling Fan               | Cast alloy aluminum    |
| Bearing                   | Single,double shielded |
| Windings                  | 100% copper            |
| Connection Type           | Reconnectable          |
| Insulation Type           | Class H                |
| Pitch                     | 2/3                    |
| Amortisseur Winding       | Full                   |
| Voltage Regulator         | AVR R448               |
| Voltage Regulator NL-FL   | $\pm 0.5\%$            |
| Underspeed Protection     | Standard               |
| Overexcitation Protection | IP23                   |
| TIF (1960 Weightings)     | <50                    |
| Exciation System          | AREP                   |

## Control Panel -Datakom

The base mounted control panel in a vibration isolated sheet steel enclosure. The control panel is equipped as follows:

- Instruments: Analogue Voltmeter, Hours Run Meter, Water pressure Meter.
- Controls: Emergency Stop Pushbutton, Voltmeter Phase Selector Switch.
- Control module: Standard collocation is Turkey Datakom 507 Auto start with AMF.



Control module Turkey Datakom 507

### Main Features:

- Δ Automatic mains failure
- Δ Engine control, Generator protection
- Δ Built in alarms and warnings
- Δ Remote Start operation available
- Δ Daily / weekly / monthly exerciser
- Δ Weekly operation schedule programs
- Δ Fuel pump control
- Δ ECU control and monitoring via J1940 CANBUS
- Δ Mains simulation
- Δ Block heater control
- Δ Field adjustable parameters
- Δ Free MS-Windows Remote monitoring
- Δ LED displays
- Δ Configurable analogue inputs
- Δ I/O expansion capability

## Sound Attenuated Enclosure/Option

### Robust Corrosion Resistant Construction

Black finish stainless steel lock and hinges  
body made from steel components treated with polyester powder coating

### Excellent Access for Maintenance

two large doors on each side  
radiator fill access plate  
lube oil and cooling water drains pipes to exterior of the enclosure

### Security and Safety

control panel viewing window in a lockable access door  
emergency stop push button (red) mounted on enclosure interior  
cooling fan and battery charging alternator fully guarded  
exhaust silencing system totally enclosed for operator safety



MINGPOWER reserves the right to modify the characteristics of its product at any time in order to incorporate the latest technological developments. The information contained in this document may therefore be changed without notice. For more technical data

Addr: P.O. Box: No.8 plot Gulou Park Jinshan  
Industrial Zone Fuzhou, China 350008  
TEL: + 86 591 83056673  
Fax : + 86 591 83855582  
sales@mingpowers.com  
www.mingpowers.com